





CL- DOT01




POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
2W	> 90	< 3	3000K	12°	126Lm
	> 80		2700K	34°	
			4000K	48°	

■ Sandy Black ■ Sandy White


LIGHT DISTRIBUTION
3000K 90Ra



h(m)	E(lx)	Φ(m)
1	273	Φ0.40
2	68	Φ0.81
3	30	Φ1.22
4	17	Φ1.63
5	10	Φ2.04



h(m)	E(lx)	Φ(m)
1	278	Φ0.72
2	69	Φ1.44
3	30	Φ2.16
4	17	Φ2.88
5	11	Φ3.60



h(m)	E(lx)	Φ(m)
1	223	Φ0.67
2	55	Φ1.35
3	24	Φ2.03
4	13	Φ2.71
5	8	Φ3.39





CL- DOT03




POWER	CRI	SDCM	CCT	BEAM	LUMINOUS FLUX
4W	> 90	< 3	3000K	12°	382Lm
	> 80		2700K	34°	
			4000K	48°	

■ Sandy Black ■ Sandy White


LIGHT DISTRIBUTION
3000K 90Ra



h(m)	E(lx)	Φ(m)
1	3782	Φ0.21
2	945	Φ0.43
3	420	Φ0.64
4	236	Φ0.86
5	151	Φ1.07



h(m)	E(lx)	Φ(m)
1	1072	Φ0.58
2	268	Φ1.16
3	119	Φ1.75
4	67	Φ2.33
5	42	Φ2.92



h(m)	E(lx)	Φ(m)
1	662	Φ0.82
2	165	Φ1.65
3	73	Φ2.47
4	41	Φ3.30
5	26	Φ4.13